


# Data sheet

## Flexible hoses VMF

Edit. august 2008



### Technical data:

Hose material PVC foil, white  
Helix spring wire  
Hose fire retardant as to  
DIN 4102-1- B2  
Temp. Range: -20 to 90  
Degr. C

Dimension mm internal	Weight/m(kg)	Thickness Mm (+0/-5%)	Bending radius mm	Max. Working pressure bar	Max vacuum bar
82	0,135	0,13	58	0,45	0,07
92	0,152	0,13	65	0,45	0,07
102	0,169	0,13	70	0,40	0,05
115	0,188	0,13	80	0,40	0,05
127	0,211	0,13	89	0,36	0,04
133	0,223	0,13	93	0,36	0,04
152	0,245	0,13	106	0,33	0,03
162	0,257	0,13	114	0,32	0,03
202	0,289	0,13	140	0,20	0,01

Application areas: Suction of kitchen fumes, air from tumble dryers and other pure air transportation. Hoses are supplied in various standard lengths: 6—15— 25 m. Other lengths and dimensions can be supplied upon request. Tests carried out at room temperature +20 degr. C

Vally Matic A/S  
Park Allé 9-11  
DK-6600 Vejen  
tel. +4575363344  
Fax +4575364820  
info@vallymatic.com  
www.vallymatic.com